

A real Italian espresso...

The caffè europa line is renowned for having introduced the two-size cup container to the mid-low cost market to offer real Italian espresso in a small cup.

DESIGN

Rounded door with architecturally-inspired motifs, backlit panel and intuitive lighting that allows the drink dispensing process to be followed.

USER INTERFACE

16 programmable selection buttons, 2 pre-select buttons to adjust sugar visually on LED bar. Monochrome graphic backlit display with programmable background colour.

DRINKS

The *espresso* version can accommodate 5 or 6 product canisters plus a coffee bean canister for those who love Italian espresso.

The *instant* version offers up to 7 product canisters and 4 mixing bowls.

A valveless pump system means problems caused by limescale are minimized. Both versions can be equipped with a cooling unit to offer cold drinks. A programming feature allows mixing speeds to be altered to adjust the density of drinks.

PERFORMANCE

A switch-mode power supply ensures consistent dosages and performance and protection against short circuits.

PROGRAMMING

Highly flexible and personal drink profiling can be achieved either manually via the machine's display or through the **rheAction** support software.

DOSAGE SETTING

Product quantities can be fine-tuned by adjusting the running times of product and pump motors.

USER FRIENDLY

Internal components can easily be removed for cleaning and maintenance.

Transparent cup containers allow quantity to be checked visually when the door is open.

ENERGY CONSUMPTION

Energy saving features include:

programmable switching on/off times to keep the machine at an energy saving stand-by temperature when inactive;
low voltage LED's to minimize consumption.

Total energy consumption is recorded starting from the first service.

MULTIMEDIA VERSION

A more innovative version with a LCD 10.4" screen to watch adv videos or provide nutrition information about the products and more.

MULTITOUCH VERSION

A further step in innovation with a central touch panel for selecting drinks, and an LCD 5.7" screen to watch adv or informative videos. A new interface for this market segment that guides the user in the choice of no less than 25 different drinks.






TECHNICAL SPECIFICATIONS

INSTANT


| SPECIFICATIONS | INSTANT ESPRESSO | |
|------------------------------------|--|-----------|
| SELECTIONS | 16+2 | 16+2 |
| TECHNICAL DATA | | |
| Height (mm) | 1830 | 1830 |
| Depth (mm) | 660 | 660 |
| Width (mm) | 575 | 575 |
| Weight (kg) | 108 | 120 |
| Max no. canisters | 7 | 7 |
| Max no. mixing bowls | 4 | 3 |
| No. of boilers | 1 | 1 |
| Boiler capacity (/) | 3,4 | 0,4 |
| Electrical supply (V-Hz) | 230-50/60 | 230-50/60 |
| Power (W) | 1700 | 1300 |
| Water connections | 3/8" male face 0.1-0.8 Mpa with anti-flood sensor | |
| STANDARD COLOUR | metallized grey (RAL 9022) | |
| CUPS | | |
| 1 turret cup dispenser Ø 70 mm | 600 | 600 |
| 2 turrets cup dispenser Ø 70 mm | 450 | 450 |
| Ø 57 mm | 500 | 500 |
| STIRRER LENGTH (MM) | 89/104 | 89/104 |
| | | |

EXAMPLE CONFIGURATION

instant version



espresso version



Wide range of customization Compatible with all payment systems

😳 rheady suite

OPTIONS Sales data collection through RFID system Data audit in accordance with EVA / DTS standars Cup sensor Colling unit for cold drinks Independent water tank kit 20 I FBT module for leaf tea

Information is related to standard machine models, further configurations are available on request. Last update 04/2012

caffè europa

rheavendors group O



| | INSTANT E | ESPRESSO |
|--|--|---------------------------------|
| SELECTIONS | 25 max | 25 max |
| TECHNICAL DATA | | |
| Height (<i>mm</i>) | 1830 | 1830 |
| Depth (<i>mm</i>) | 660 | 660 |
| Width (mm) | 575 | 575 |
| Weight (kg) | 108 | 120 |
| Max no. canisters | 7 | 7 |
| Max no. mixing bowls | 4 | 3 |
| No. of boilers | 1 | 1 |
| Boiler capacity (/) | 3,4 | 0,4 |
| Electrical supply (V-Hz) | 230-50/60 | 230-50/60 |
| Power (W) | 1700 | 1300 |
| Water connections | | face 0.1-0.8 ti-flood sensor |
| STANDARD COLOUR | | ized grey _ 9022) |
| CUPS | (| · / |
| 1 turret cup dispenser Ø 70 mm | 600 | 600 |
| 2 turrets cup dispenser Ø 70 mm | 450 | 450 |
| Ø 57 mm | 430 500 | 500 |
| | 300 | 000 |
| STIRRER LENGTH (MM) | 89/104 | 89/104 |
| instant version 5500 gr. 1.190 gr. 1200 gr. 6500 gr. 1300 gr. | 4000 gt. 4400 g | 1 |
| CHOCOLAFE AILK INSFANT COFF SUGAR BARLEY | GINSEMG | |
| ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | ç | |
| short coffee capp-ciocc chocolate | long white barley | |
| long coffee milky coffe tea short white coffee coffee with choco short barley cappuccino milk short white barley | short ginseng short white ginseng long white ginseng | |
| | | |
| espresso version | \sim | ~ |
| espresso version Serversion | 4000LATE | κ. |
| | CHOCOLAIE | |
| Coffee Beans Sugar | LEA CHOCOLAIE | |
| Alone and a service and a serv | LEV CHOCOTVIE | e coffee |
| espresso capucino chocolate lang coffee mily coffee ta | LEA CHOCOLAIE | |
| espresso cappulato tea | EX CHOCOLARE | |
| espresso att while espresso and while espresso Central touch panel 10,4" and side displ Wide range of customization | decaf, short white short ginseng short white ginseng long white ginseng | |
| espresso long ondie bary white espresso long ondie with range of customization Compatible with all payment systems Or practice | decaf, short white short ginseng short white ginseng long white ginseng | |
| espresso and the espresso and the espresso contrastile espresso contrastile espresso milk office tage define the espresso milk office tage define tage | decaf. short white short white ginseng long white ginseng ay LCD 5,7" | |
| espresso espresso long coffee short white espresso relation of the spresso relation of the | decaf. short white short white ginseng long white ginseng ay LCD 5,7" | |

caffè europa multitouch

rheavendors group O





| TECHNICAL SPECIFICATIONS | INSTANT I | ESPRESSO |
|-----------------------------|--|-----------|
| SELECTIONS | 16+2 | 16+2 |
| TECHNICAL DATA | | |
| Height (mm) | 1830 | 1830 |
| Depth (mm) | 660 | 660 |
| Width (mm) | 575 | 575 |
| Weight (kg) | 108 | 120 |
| Max no. canisters | 7 | 7 |
| Max no. mixing bowls | 4 | 3 |
| No. of boilers | 1 | 1 |
| Boiler capacity (I) | 3,4 | 0,4 |
| Electrical supply (V-Hz) | 230-50/60 | 230-50/60 |
| Power (W) | 1700 | 1300 |
| Water connections | 3/8" male face 0.1-0.8 Mpa with anti-flood sensor | |
| STANDARD COLOUR | metallized grey (RAL 9022) | |
| CUPS | | |
| 1 turret cun dispenser | | |

| STIRRER LENGTH (MM) | 89/104 | 89/104 |
|------------------------------------|--------|--------|
| Ø 57 mm | 500 | 500 |
| 2 turrets cup dispenser Ø 70 mm | 450 | 450 |
| 1 turret cup dispenser Ø 70 mm | 600 | 600 |
| CUPS | | |

EXAMPLE CONFIGURATION







Central TFT 10,4" color Wide range of customization Compatible with all payment systems 🔾 rheady suite

OPTIONS

Sales data collection through RFID system Data audit in accordance with EVA / DTS standars Cup sensor Colling unit for cold drinks Independent water tank kit 20 I FBT module for leaf tea

Information is related to standard machine models, further configurations are available on request. Last update 04/2012

caffè europa multimedia

rheavendors group O

caffè europa combo

caffè europa machines can be combined to offer the right solution to satisfy every need and create a complete refreshment station of first-class design.



| rheavendors | group O | | |
|------------------------------------|---------------------|--|--|
| Rhea Vendors Group S.p.A. | | | |
| Via Trieste 49, Caronno Pertusella | a (VA) 21042, Italy | | |

| Benelux | Deutschland |
|---------------|---|
| rheavendors O | servomat |
| benelux | steigler |
| France | Österreich |
| rheavendors O | rheavendors O |
| france | servomat A |
| Pocciui | United Kingdom |
| rheavendors O | rheavendors O |
| east | servomat UK |
| | rheavendors O benelux France rheavendors O france Poccini rheavendors O |

caffe europa europa snack side multimedia



snac cafe

----- N CE per maggiori informazioni rheavendors.com

